



Furby Outer Shell Replacement

Open the back panel of your device to start working on the components.

Written By: Jordan Castillo



INTRODUCTION


The device has fabric and an outer shell that needs to be removed. Removing the connector tabs are the hardest part of this guide.



TOOLS:




- [1.0 mm Flathead Screwdriver](#) (1)
 - [Tweezers](#) (1)
 - [Phillips #0 Screwdriver](#) (1)
 - [Metal Spudger Set](#) (1)
-

Step 1 — Outer Shell



- Use a flathead screwdriver to remove the two 10mm screws on the base of the Furby.



Step 2



- Use a Phillips #0 driver to unscrew the eight 10mm screws.
- Remove the base ring after unscrewing all the screws.




⚠ Be careful when lifting the base ring from the Furby. There are sharp edges that hold the base ring in place.

Step 3





- Unhook the white ribbon from the tab on the base.

Step 4






- Roll the Furby's fur downward.
- Disconnect the now exposed red wire.

Step 5



- Locate the two middle clips first.
- Locate the two remaining clips on Furby's sides, they are opposite each other.
- Orient the Furby upside down with the tail facing away from you.

Step 6



- Insert a metal prying tool directly into the clip opening.
- Press upward into the clip. At the same time, use your other hand to pull away the plastic seam from the Furby's body.
- Repeat the previous step to remove the remaining three clips.

Step 7



- Locate the two 10mm screws and remove them with the Phillips #0 head screwdriver.
- Lift up on the fur covering until the face of the Furby is exposed.

Step 8



- Orient the Furby on its side to where the beak is facing left and locate the edge of the aluminum tape.
- Lift tape gently and peel back until the tape is nearly removed.


⚠ Do not pull on the yellow wire located on the opposite end of the tape.

Step 9





- Locate the four 10mm screws. Two on either side of body, and two on top of back plate, around the tape.
- Remove the 10mm screws with the Phillips#0 screwdriver.

Step 10




- Peel the tape gently, grabbing it from the bottom edge and folding the tape upward.
- ⓘ Peel the tape up until it is nearly detached from the black case.

Step 11



- Orient the Furby face down, with the base facing away from you.
- Locate the clips below the ears.
- Repeat the technique used in Step 6. Create leverage using a metal prying tool to press upward into the clip, while also pulling back on the clip itself.

Step 12



- Remove the loose, plastic back panel by pulling the panel away from Furby's body.

This document was last generated on 2017-06-19 03:13:30 AM.